



































Audi RS 6		Typ 4F
MJ 2008 > MJ 2011		
VIN	4F.8 N 000 001	4F.B N 999 999
	e1 * 2001/116 * 0276 *	

<b>5,0l 426 kW</b>						
					 	
	255/40 ZR 19 100Y Extra Load	9J x 19 ET 29	R01		2,5	2,
	275/35 ZR 20 102Y Extra Load	9,5J x 20 ET 36	R01		2,7	2,
	255/40 R 19 100V Extra Load	9J x 19 ET 38	R01		3,0	3,
	265/35 R 20 99V Extra Load	9J x 20 ET 38	R01		3,0	3,
	275/35 R 20 102V Extra Load	9,5J x 20 ET 36	R01		3,0	3,

R01- Speziell auf das Fahrzeug abgestimmte Reifen. Wir empfehlen Reifen mit dieser Bezeichnung zu fahren.

<b>MJ 2008 &gt;</b>			
 <b>5 x 120 Nm</b>	 <b>Ø 112 mm</b>	 <b>Ø 57 mm</b>	
			
4F0 601 025 BS 2WY 9J x 19 H2 ET 38 max. 715kg 	4F0 601 025 BT 2XM 9J x 20 H2 ET 38 max. 715kg 	4F0 601 025 BR 2YY 9,5J x 20 H2 ET 36 max. 715kg 	

			
			
4F0 601 025 BQ CW3 9J x 19 H2 ET 29 max. 715kg 	4F0 601 025 BR CY6 9,5J x 20 H2 ET 36 max. 715kg 	4F0 601 025 CS F24 9,5J x 20 H2 ET 36 max. 715kg 	4F0 601 025 L 9,5J x 20 H2 ET max. 715kg 
			
4F0 601 025 CT F12 9J x 19 H2 ET 29 max. 715kg 