

Tabelle1

Wednesday
4B0 906 018 AG

26 September
1.8L R4/5VT G01 0005

2012 20:04:32

Group A:		002			
		UPM	Last	Einspritzzeit	anges. Luftma
MARKER	TIME STAMP	/min	%	ms	g/s
	1.12		760 19.5	1.64	3.17
	2.49		800 20.3	2.05	3.11
1	4.13		800 20.3	2.05	3.11
	5.92		800 19.5	2.05	2.81
	7.37		1520 78.2	8.20	20.50
	9.00		800 27.1	2.87	6.03
	10.74		2400 45.1	3.28	15.28
	12.18		1920 82.7	8.20	30.42
	13.68		1920 28.6	4.51	21.89
	15.53		1800 60.9	5.33	21.00
2	17.07		2040 85.7	8.20	35.22
	18.57		2440 113.5	11.89	55.44
5	20.43		3000 136.1	14.76	75.25
7	21.86		3600 151.1	16.81	103.39
10	23.38		4120 152.6	16.40	121.97
13	25.12		4680 142.1	15.99	126.64
15	26.82		5240 136.8	16.81	138.67
17	28.26		5640 132.3	17.22	143.75
20	30.03		6000 127.1	16.81	145.47
24	31.79		6320 121.8	16.81	146.75
	33.27		5200 16.5	3.28	34.03
	34.92		3040 14.3	0.00	8.31
	36.61		1280 29.3	3.28	7.00
	38.06		3200 12.0	0.00	7.83
	39.67		3040 12.0	0.00	6.94
	41.51		2880 12.0	0.00	7.28
	42.96		2760 12.8	0.00	6.47
25	44.55		2640 12.8	0.00	6.67
28	46.34		2560 12.8	0.00	6.75
33	47.84		2440 13.5	0.00	6.36
35	49.36		2160 12.8	0.00	5.47
36	51.32		1840 12.0	0.00	4.44
	52.90		1600 12.8	0.00	4.00
	54.45		1400 12.8	0.00	3.47
	56.24		1280 12.8	0.00	3.17

Tabelle1

57.74	1240 12.8	1.64	3.06
59.25	1000 13.5	1.23	3.03
61.09	880 19.5	1.64	3.03

Tabelle1

Group B:	001				Group C:	010
sse	UPM	Temperatur	Lambda	Bin. Bits		UPM
TIME					TIME	
STAMP	/min	°C	%		STAMP	/min
1.57	760	91.0	7.0	11111111	0.62	760
2.97	800	91.0	10.2	11111111	1.97	760
4.74	800	92.0	14.1	11111111	3.48	760
6.42	1600	92.0	10.2	11101111	5.42	800
7.87	1160	92.0	0.0	11110111	6.91	1720
9.64	1640	92.0	-1.6	11101011	8.36	960
11.23	2040	92.0	0.0	11110101	10.19	1880
12.67	2120	93.0	-14.8	11101001	11.66	1680
14.33	1640	93.0	0.0	11100011	13.17	2320
16.02	1840	92.0	-14.8	11101011	14.91	1720
17.57	2160	92.0	-6.3	11101001	16.53	1920
19.18	2600	92.0	0.0	11100001	18.06	2280
20.91	3200	92.0	0.0	11100001	19.82	2760
22.36	3760	92.0	5.5	11100001	21.35	3400
23.87	4320	92.0	0.0	11100001	22.88	4000
25.74	4880	91.0	0.0	11100001	24.54	4520
27.27	5360	91.0	0.0	11100001	26.27	5040
28.77	5760	91.0	0.0	11100001	27.77	5520
30.64	6120	90.0	0.0	11100001	29.41	5880
32.28	6440	90.0	0.0	11100001	31.23	6240
33.75	4480	90.0	0.0	11110001	32.76	5960
35.51	2280	90.0	0.0	11110101	34.28	3720
37.11	3400	91.0	0.0	11100101	36.11	1520
38.55	3160	92.0	0.0	11110101	37.58	3240
40.31	3000	92.0	0.0	11110101	39.06	3080
42.03	2840	92.0	0.0	11110101	40.92	2960
43.44	2720	92.0	0.0	11110101	42.48	2800
45.21	2600	91.0	0.0	11110101	43.95	2680
46.82	2520	91.0	0.0	11110101	45.80	2600
48.35	2360	90.0	0.0	11110101	47.30	2520
50.00	2080	90.0	0.0	11110101	48.85	2280
51.86	1720	90.0	0.0	11110111	50.62	1960
53.44	1520	90.0	0.0	11110111	52.40	1680
55.09	1360	90.0	0.0	11110111	53.95	1480
56.78	1240	90.0	0.0	11110111	55.71	1320

Tabelle1

58.24	1200 90.0	0.0	11110111 57.26	1240
59.84	840 90.0	-2.3	11111111 58.74	1200
61.71	1040 90.0	0.8	11111111 60.51	760

Tabelle1

Last	Last	Zündwinkel
%	%	°v.OT
20.3	1.2	10.5
21.1	1.6	10.5
19.5	1.2	16.5
20.3	1.6	7.5
74.4	16.1	7.5
23.3	1.2	7.5
82.7	84.7	10.5
78.9	46.7	9.0
62.4	14.1	22.5
66.9	14.1	15.0
68.4	22.0	17.3
106.8	100.0	10.5
122.6	100.0	12.8
153.4	100.0	11.3
151.1	100.0	12.8
146.6	100.0	14.3
137.6	100.0	16.5
134.6	100.0	14.3
128.6	100.0	18.0
122.6	100.0	18.8
11.3	6.7	12.8
15.8	6.3	3.0
17.3	1.6	2.3
12.0	4.3	32.3
12.0	3.9	2.3
12.0	3.9	1.5
12.0	3.9	1.5
12.8	3.5	1.5
12.8	3.5	1.5
12.8	3.5	1.5
12.8	3.1	0.8
13.5	2.7	0.8
12.0	2.0	1.5
12.8	1.6	3.0
12.0	1.2	4.5

Tabelle1

12.0	1.2	4.5
12.8	1.2	10.5
20.3	1.6	14.3