

Reifen Dimension	Li	Geschw.Kl. Extralast (XL)	M+S Standard	Runflat	Rad	IS [mm]	Stahlrad LM-Rad	Schnäckette mögl. (HA)	BMW 1er 5-und 3-türer (F20/F21)									
									114i	116i	116d	116ed	118i	118d	120d	125i	125d	M135i
					N13B16K0	N13B16U0	N47D20K1	N47D16U1	N13B16M0	N47D20U1	N47D20O1	N20B20M0	N47D20T1	N55B30O0				
Sommer:																		
195/55 R16	87	H	x x		6,5Jx16 H2	33	x	x	x	x	x	-	-	-	-	-	-	-
195/55 R16	87	V	x x		6,5Jx16 H2	33	x	x	-	-	-	-	x	x	-	-	-	-
205/55 R16	91	V	x x		7Jx16 H2	40	x	x	-	-	-	x *)	-	-	x	-	-	-
205/55 R16	91	V	x x		7Jx16 H2	40	x	x	x	x	x	x *)	x	x	x	-	-	-
205/55 R16	91	W	x x		7Jx16 H2	40	x	x	-	-	-	-	-	-	-	-	-	-
205/55 R16	91	W	x x		7Jx16 H2	40	x	x	-	-	-	-	-	-	-	-	-	-
205/50 R17	89	V			7Jx17 H2	40	x	x	x	x	x	-	x	x	-	-	-	-
205/50 R17	89	W			7Jx17 H2	40	x	x	-	-	-	-	-	-	x	x	x	-
225/45 R17	91	W			7,5Jx17 H2	43	x	x	x	x	x	-	x	x	x	x	x	-
VA: 225/45 R17	91	W			7,5Jx17 H2	43	x	x	x	x	x	-	x	x	x	x	x	-
HA: 245/40 R17	91	W			8Jx17 H2	53	x	x	x	x	x	-	x	x	x	x	x	-
VA: 225/40 R18	88	Y			7,5Jx18 H2	45	x	x	x	x	x	-	x	x	x	x	x	x
HA: 245/35 R18	88	Y			8Jx18 H2	52	x	x	x	x	x	-	x	x	x	x	x	-
VA: 225/40 R18	88	Y	x x		7,5Jx18 H2	45	x	-	-	-	-	-	-	-	-	-	-	x
HA: 245/35 R18	88	Y	x x		8Jx18 H2	52	x	-	-	-	-	-	-	-	-	-	-	x
VA: 225/35 R19 XL	88	Y	x		7,5Jx19 H2	45	x	x	x	x	x	-	x	x	x	x	x ***)	
HA: 245/30 R19 XL	89	Y	x		8Jx19 H2	52	x	x	x	x	x	-	x	x	x	x	x ***)	
Winter:																		
195/55 R16	87	H	x x x		6,5Jx16 H2	33	x	x	x	x	x	-	x	x	x	-	-	-
205/55 R16	91	H	x x x		7Jx16 H2	40	x	x	x	x	x	x	x	x	x	x	x	-
205/50 R17	89	H	x x		7Jx17 H2	40	x	x	x	x	x	-	x	x	x	x	x	x
225/45 R17	91	H	x x		7,5Jx17 H2	43	x	x	x	x	x	-	x	x	x	x	x	x
225/40 R18 XL	92	V	x x		7,5Jx18 H2	45	x	x	x	x	x	-	x	x	x	x	x	x
Reserverad:																		
125/80 R17	99	M			3,5Bx17 H2	8	x		x	x	x	x	x	x	x	x	x	x

Zusätzl. Informationen:

*) nur Standard-Reifen

**) nicht zulässig in Verbindung mit SA 235 Anhängerkupplung

- = nicht freigegeben

X = zulässige Rad-/Reifendimension

Radschrauben: M14x1,25