

All dimensions in inches (mm) unless otherwise stated.





	Specifications	2WD CC15906	2WD CC25906	4WD CK15906	4WD CK25906
A	**Wheelbase**	130.00 (3302)	130.00 (3302)	130.00 (3302)	130.00 (3302)
B	**Overall length**	219.30 (5570)	219.30 (5570)	219.30 (5570)	219.30 (5570)
C	**Body width**	78.90 (2004)	79.80 (2027)	78.90 (2004)	79.80 (2027)
D	**Overall height,** with luggage rack	73.60 (1869)	76.40 (1941)	75.40 (1915)	76.50 (1943)
	Head room, front	40.70 (1034)	40.70 (1034)	40.70 (1034)	40.70 (1034)
	Head room, center	39.00 (991)	39.00 (991)	39.00 (991)	39.00 (991)
	Head room, rear	38.60 (980)	38.60 (980)	38.60 (980)	38.60 (980)
	Shoulder room, front	65.20 (1656)	65.20 (1656)	65.20 (1656)	65.20 (1656)
	Shoulder room, center	65.10 (1654)	65.10 (1654)	65.10 (1654)	65.10 (1654)
	Shoulder room, rear	64.40 (1636)	64.40 (1636)	64.40 (1636)	64.40 (1636)
	Hip room, front	61.40 (1560)	61.40 (1560)	61.40 (1560)	61.40 (1560)
	Hip room, center	61.30 (1557)	61.30 (1557)	61.30 (1557)	61.30 (1557)
	Hip room, rear	49.20 (1250)	49.20 (1250)	49.20 (1250)	49.20 (1250)
	Leg room, front	41.30 (1049)	41.30 (1049)	41.30 (1049)	41.30 (1049)
	Leg room, center	39.10 (993)	39.10 (993)	39.10 (993)	39.10 (993)
	Leg room, rear	36.10 (917)	36.10 (917)	36.10 (917)	36.10 (917)
BA	**Front bumper to axle**	37.00 (940)	37.00 (940)	37.00 (940)	37.00 (940)
	Ground to top of rear load floor	31.20 (792)	32.50 (826)	31.00 (787)	33.20 (843)
	Load floor length, to front seat, at floor	104.60 (2657)	104.60 (2657)	104.60 (2657)	104.60 (2657)
	Load floor length, to center seat, at floor	69.60 (1768)	69.60 (1768)	69.60 (1768)	69.60 (1768)
	Load floor length, to rear seat, at floor	36.10 (917)	36.10 (917)	36.10 (917)	36.10 (917)
	Inside width, at floor	49.20	49.20	49.20	49.20

All dimensions in inches (mm) unless otherwise stated.

Specifications		2WD CC15906	2WD CC25906	4WD CK15906	4WD CK25906
		(1250)	(1250)	(1250)	(1250)
Inside width, between wheelhousing		49.10 (1247)	49.10 (1247)	49.10 (1247)	49.10 (1247)
Cargo area height		40.50 (1029)	40.50 (1029)	40.50 (1029)	40.50 (1029)
Ground clearance, front		9.80 (249)	8.10 (206)	9.80 (249)	8.40 (213)
Ground clearance, rear		8.40 (213)	7.10 (180)	8.40 (213)	7.10 (180)

Published dimensions indicated are without optional equipment or accessories. Additional accessories or equipment ordered at the customer's request can result in a minor change in these dimensions.

	2WD CC15906	2WD CC25906	4WD CK15906	4WD CK25906
Specifications				
Front shock absorber diameter, in. (mm)	1.81 (46)	1.38 (35)	1.81 (46)	1.38 (35)
Front stabilizer bar diameter, in. (mm)	1.25 (32)	1.25 (32)	1.18 (30)	1.18 (30)
Rear shock absorber diameter, in. (mm)	1.81 (46)	1.38 (35)	1.81 (46)	1.38 (35)
Rear stabilizer bar diameter, in. (mm)	1.18 (30)	--	1.18 (30)	--
Turning diameter, curb-to-curb, ft. (m)	43.0 (13.1)	44.5 (13.6)	43.7 (13.3)	44.3 (13.5)
Turning diameter, curb-to-curb, with (NYS) 4-wheel steering, ft. (m)	--	36.5 (11.1)	--	36.5 (11.1)
Capacities				
Front axle, lbs. (kg)	3400 (1542)	4100 (1860)	3925 (1780)	4500 (2041)
Front spring capacity, lbs. (kg)	3150 (1429)	4100 (1860)	3600 (1633)	4500 (2041)
Rear axle, lbs. (kg)	4000 (1814)	5500 (2495)	4000 (1814)	5500 (2495)
Rear spring capacity, lbs. (kg)	4000 (1814)	6000 (2722)	4000 (1814)	6000 (2722)
Curb weight, lbs. (kg)	5268 (2390)	5773 (2619)	5474 (2483)	6073 (2755)
Curb weight, with (NYS) 4-wheel steering, lbs. (kg)	--	6138 (2784)	--	6439 (2921)
Cargo volume, cu. ft. (liters)	131.6 (3726.9)	131.6 (3726.9)	131.6 (3726.9)	131.6 (3726.9)
Payload[1], lbs. (kg)	1732 (786)	2827 (1282)	1726 (783)	2527 (1146)
Payload, with (NYS) 4-wheel steering, lbs. (kg)	--	2462 (1117)	--	2161 (980)
Gross Vehicle Weight Rating (GVWR), lbs. (kg)	7000 (3175)	8600 (3901)	7200 (3266)	8600 (3901)
Front Gross Axle Weight Rating (GAWR), lbs. (kg)	3200 (1452)	3800 (1724)	3600 (1633)	4180 (1896)
Rear Gross Axle Weight Rating (GAWR), lbs. (kg)	4000 (1814)	5500 (2495)	4000 (1814)	5500 (2495)
Fuel capacity, approximate, gallon (liters)	31 (117)	37 (140)	31 (117)	37 (140)
Seating capacity (front/center/rear)	3/3/3	3/3/3	3/3/3	3/3/3

1. Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo.