AP00.20-P-1228TM	OVERVIEW for service sheet	08.11.2016

Model 231

	Ser	vice A			
	Ser	vice B			
	Plus pa	ackage			
	For eve	ery service (equipment specific)		-	
	For the	first time at 3,000 km	2		- French
	Every 6	50,000 km	Maria I	AT	
	Service	e 3 At every service			8
	Service	4 Every 2 years			
	Service	8 Every 20,000 km / 3 years			
	Service	e 11 Every 150,000 km/5 years			
	Service	2 12 Every 20,000 km/3 years			
	Service	e 12 Every 60,000 km/3 years			P00.00-4901-11
	Service	e 13 every 200,000 km / 10 years			P00.00-4901-11
	Service	e 14 Every 50,000 km/3 years			
	Service	2 20 Every 60,000 km/4 years			
Custom	ner		Order number		
		ate number	Current mileage		
			Current mileage		
Comple	etion tim	ne/date			
Notes/e	explana	tions			
The foll	owina a	activities are hereby confirmed:			
- Comp	letion o	f relevant service operations			
Signatu	ıre				
			Innut condition not OK.		
Α	В		Input condition not OK:	\otimes	
Compl					
\times	\times				
•	-			•	
		Service reception			
		The completely processed pre-order is available for service on the vehicle		\circ	
			i To be performed by the Service Advisor (where market-		
			specific conditions require).		
			The service scope is only completely performed when all		
			acceptance items and the maintenance items listed in the		
			service sheet have been fully processed.		
		Brake system	p:000000u.		
		Perform brake test and enter the result in the table		\circ	
				AP42	2.00-P-4290BA

		Vehicle exterior Check condition of vehicle exterior		0	
		Check condition of windshield		\circ	AP60.00-P-0050RK
		Check condition of wiper blades		0	AP67.10-P-6750A
	П	Check exterior lights for proper operation		\bigcirc	AP82.30-P-8253G
	_	Check operation of headlamp range		\circ	AP82.10-P-8252EW
		adjustment	Vehicles with xenon or dynamic LED headlamps or headlamp range controller on the exterior lights switch	O	
		Check/correct headlamp adjustment		0	AP82.10-P-8250EW
			i On vehicles equipped with level control or Xenon or dynamic LED headlamps, headlamp adjustment is to be invoiced as an additional operation.		AP82.10-P-8260R
		Vehicle interior Check windshield wipers, windshield washer system and headlamp cleaning system for proper operation		0	AD00 00 D 0050DIV
		Replace activated charcoal dust filter			AP82.30-P-8252RK
		Check warning and function indicator lamps in instrument cluster		0	AP83.00-P-8384CW
		Read out map data version from navigation system, check update			AP54.30-P-5451RK
			i Enter map data status:		AP82.85-P-8251B
		Read out maintenance data from instrument cluster, note and reset service indicator			AP00.20-P-0043EL
П	П	Engine compartment Clean water drain			AF00.20-F-0043EL
		Brake system: Check fluid level		\bigcirc	AP82.35-P-8232A
Ц				O	AP42.10-P-4210V
		Active Body Control (ABC): Check fluid leve	With code 487 (Active Body Control	0	AP32.50-P-3213SX
		Check low-temperature circuit coolant level	(ABC))	0	
			Engine 157, 278 Engine 276.8 Engine 279		AP20.30-P-2052G AP20.30-P-2052H AP20.30-P-2052I
		Check all visible parts in engine compartment for damage and leaks		0	
		Check visible area of poly-V belt for wear		0	AP00.20-P-0055EW
		Underside of vehicle	Engine 157, 276, 278, 279		AP13.22-P-1352EW
		Check all visible parts of vehicle underside for damage and leaks		\bigcirc	
			i The country-specific regulations for mobility and body shell complaints apply.		AP00.20-P-0054EW

		Check track rod and drag link linkage for play, check boots		0	
		Check front axle ball joint for play, check boots		0	AP46.00-P-4653EW
		Check condition of propeller shaft and flex disks		0	AP33.20-P-3353SX
	П	Assess condition and tread depth of tires		\circ	AP41.10-P-4152EW
		then enter into table Assess condition of brake pads and enter		\bigcirc	AP40.10-P-4052E
		into table Assess condition of brake disks and enter		\circ	AP42.10-P-4252RK
Ш		into table		Ō	AP42.10-P-4256EW
		Check tires for damage and crack formatio and enter result in table	n	0	AP40.10-P-4051EW
		Tires Plus package Correct tire pressure and enter set tire			
		pressure in table		<u> </u>	AP40.15-P-4061A
	_	Trunk Plus package Check/correct spare wheel tire pressure ar	od		
		enter set tire pressure in table	Vehicles with spare tire	O	45404554004
		Check TIREFIT tire sealant		\bigcirc	AP40.15-P-4061A
Ш			Vehicles fitted with TIREFIT	O	AP40.10-P-4054R
			i Enter TIREFIT expiration date here:		AF40.10-F 40041V
			Replace TIREFIT, invoice as additional operation.		
		Check first aid bag		0	
			i Enter first aid bag expiration date here:		AP68.00-P-6850EW
			Replace first aid bag, invoice as an additional operation.		
		Check trunk illumination for proper operation		0	
	_	Engine compartment Plus package Windshield washer system: Check/correct			
Ш		fluid level			AP82.35-P-8210EW
			Use summer/winter cleaner as well as its mixing ratio to match the ambient temperature. With low fill level		
			Add cleaner subject to separate invoice.		
		Vehicle interior Plus package		,	
		Check lamps in the instrument cluster and interior illumination for proper operation		0	AP54.30-P-5453RK
		Vehicle interior For every service (equipment specific)			
		Replace battery for KEYLESS-GO key			

			After consultation with customer	
		Underside of vehicle	With code 889 (KEYLESS-GO)	
		For the first time at 3,000 km		
		Rear axle: Perform oil change		
			With code 471 (Manual locking differential)	AP35.00-P-3501CMG
		Engine compartment Every 60,000 km		
П	П	Replace spark plug connector		
Ш			Engine 157, 276, 278	AR15.12-P-2003RK
			Engine 137, 276, 276 Engine 279	AR15.12-P-2003RKC
		Engine compartment Service 3 At every service		
\Box		Engine: Change oil and filter		
ш			Engine 157	AP18.00-P-0101EWG
			Engine 276	AP18.00-P-0101CWZ
			Engine 278	AP18.00-P-0101EW
		Engine compartment	Engine 279	AP18.00-P-0101BA
		Service 4 Every 2 years		
		Brake system: Replace brake fluid		
				AP42.00-P-4280V
		Engine compartment Service 8 Every 20,000 km / 3 years		
\Box		Replace air filter element		
Ш	ш	·		
			Engine 157, 278 Engine 276.8	AP09.10-P-0980AB AP09.10-P-0980E
			ENGINE 276.9	AP09.10-P-0980MM
			Engine 279	AP09.10-P-0980SZ
		Underside of vehicle Service 8 Every 20,000 km / 3 years		
П	П	Rear axle: Perform oil change		
			With code 471 (Manual locking differential)	AP35.00-P-3501CMG
		Trunk Service 11 Every 150,000 km/5 years		
П	П	Replace fuel filter		
			Engine 157, 276, 278, 279	AP47.20-P-0780RK
		Engine compartment		-
_	_	Service 12 Every 20,000 km/3 years Replace spark plugs		
Ш	ш	replace spain plage		
			Engines with direct injection Engine 157, 276, 278	AP15.10-P-1580V
		Engine compartment		74 10.101 10007
_	_	Service 12 Every 60,000 km/3 years		
		Replace spark plugs		
			Engines without direct injection	AD45 40 D 4500AAA
		Underside of vehicle	Engine 279	AP15.10-P-1580AAA
		Service 13 every 200,000 km / 10 years		
		Replace main circuit coolant		
			Engine 157, 276, 278	AP20.00-P-2080V
		Replace low-temperature circuit coolant		
		·		
			Engine 157, 276.8, 278 Engine 279	AR20.00-P-1142RK AP20.00-P-2083A
		Underside of vehicle Service 14 Every 50,000 km/3 years		25.55 (2550) (
		Replace main circuit coolant		
Ш		·		A DOO OO T
			Engine 279	AP20.00-P-2080AC

			Service 2	-	00 km/4 years						
			Automatic transmission: Carry out oil and filter change								
				90			TRANSMISSIC	ON 722.9)		AP27.00-P-2702W
							TRANSMISSIO				AP27.00-P-2702B
								,,,, <u>_</u>			7.1.27.100 7.2.022
Brake '	values										
					Left				Right		
Front Rear											
	g brak	Δ									
Condit	ion/trea	ad depth of tir			ble field w	ith X or option	ally, enter trea	1		L	_
<u> </u>		14 11 41	Right	front		Left front		Right r	ear	L	_eft rear
Conar OK.	tion an	d tread depth									
Wear l		ached /									
Unusı	ıal wea	r pattern									
reache	ed / exc	/ mileage ceeded ection only)									
		orake linings (1		D:1-4		1.	- \$4
Condi	tion in	visible area	Right	tront		Left front		Right r	ear	L	Left rear
Wear I		ached /									
	(oil, g	rease, etc.)/									
Condit	ion of b	orake disks (M	ark ap		eld with X)	Left front		Right r	ear	L	_eft rear
Condi OK.	tion in v	visible area									
score	marks,	jed (e.g.: cracks,									
deeply	/ conto	ippings, ured ridging									
		ke disks)									
Soiled	(oil, g	rease, etc.)									
Set tire	press	ure in bar or յ	osi								
	-	·		Front axl	Δ		Rear axle			Spare w	vheel
bar/ps	i i			FIOIIL AXI	-		iveal axie			Spare W	VIIGEI
Jai/þ5	''										